

Beta CHEMICALS



CATALOGUE **2022**

Tightening a bolt is not always enough to guarantee secure tightening. Cleaning, lubrication and sealing are also necessary.

The range comprises anaerobic sealants, cyanoacrylate adhesives and aerosol cans for maintaining, cleaning and lubricating mechanical parts.

Anaerobic Products

Anaerobic products allow complete filling of small superficial irregularities in metal, so that mechanical stress can be distributed throughout the connecting surface. They harden in total absence of oxygen and completely seal joints or threads from water, gas, oil, fuel and industrial fluids.

They are available in three different strengths - high (H), medium (M) and low (L) - and in different packs, to satisfy different needs.

Silicone sealant

- Enables permanent elastic sealing.
- Replaces preformed gaskets.

- The convenient dispenser allows easy (one-coated), accurate, uniform spreading of the product.
- Polymerizes by reacting with atmospheric moisture and forms an elastic, durable gasket.

Instant Glue

Adhesive based on ethyl cyanoacrylate, for structural joints in a number of materials.

Aerosols

A wide range of products in spray cans, for use for unlocking, greasing, lubricating, cleaning, galvanizing and sanitizing purposes.

Liquids

Developed to remove encrustations and rust from mechanical parts and metal objects. Ideal for use with ultrasonic cleaning tanks 1895.

Index

| | |
|--------------------------|----|
| Spray | 03 |
| Adhesive products | 13 |
| Anaerobic products | 14 |
| Silicone sealants | 22 |
| Liquids | 23 |

ATTENTION

Countries where the products of the Beta Chemicals range are allowed to be distributed: Austria, Belgium, China, Czech Republic, France, Hungary, Italy, Netherlands, Poland, Portugal, Republic of Ireland, Slovakia, Slovenia, Spain, Switzerland, United Kingdom, United Arab Emirates.

Spray



9710

7-in-1 multipurpose unlocking lubricant

1. **Unlocking:** dissolves rust from nuts, bolts and gears in general.
2. **Lubricating:** suitable for all mechanical parts subject to stress.
3. **Detergent, degreasing:** removes grease and oil from metal surfaces.
4. **Rust protective:** forms a film protecting against corrosion from weather.
5. **Deoxidizing, for electrical contacts:** reactivates contacts and prevents short circuits.
6. **Waterproof:** removes water and humidity from all surfaces.
7. **Antifreezing:** highly resistant to low temperatures (up to -40 °C).

Fitted with a special valve allowing supply when spray can is upside down. Silicone-free.



| Item | Size |  |  |
|------|--------|---------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|
| 9710 | 400 ml | 12 | 097100040 |

Adjustable Straw

ADJUSTABLE STRAW allows - through a special modular straw - application on parts which would be difficult to reach with a standard dispenser.



LubriBeta

UNIVERSAL

9712



Unlocking lubricant, super-penetrating

Unlocking, deoxidizing, highly penetrating, for quick rust and oxidation removal from nuts, bolts, screws and gears.

Waterproof, for water and humidity removal from treated parts.

Highly resistant to cold and heat (-40°C ÷ +150°C).



| Item | Size |  |  |
|------|--------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|
| 9712 | 400 ml | 12 | 097120040 |

Ultra SBLOCK

9720



Multipurpose grease

Particularly useful for lubricating chains, gears and moving metal parts as well as hinges, locks and pivots. Resistant to friction and weather.

Highly resistant to high temperatures (up to 210°C).

Highly adhesive. Does not drip.



| Item | Size |  |  |
|------|--------|---------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|
| 9720 | 400 ml | 12 | 097200040 |



Multi GREASE

9722

White lithium grease

Based on grease with lithium, titanium and zinc oxide soaps. Ideal for gears, bearings, joints and parts subject to mechanical movement in general. Particularly useful for lubricating and protecting mechanical parts in marine applications. Highly resistant to water, sea salt, weather and high temperatures (up to 150°C). Does not drip.



| Item | Size |  |  |
|------|--------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|
| 9722 | 400 ml | 12 | 097220040 |



Lithium
GREASE

9724

PTFE based grease

Lubricating grease mixed with PTFE. Particularly useful for lubricating industrial chains and mechanical movements subject to heavy stress and low rotation speeds. Also suitable for hinges, locks, drawer slides, gates and applications on plastics and rubber. Totally colourless. Waterproof and resistant to oxidation. Highly resistant to cold and heat (-30°C to +220°C).



| Item | Size |  |  |
|------|--------|---------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|
| 9724 | 400 ml | 12 | 097240040 |



PTFE
GREASE

9726

Copper grease

Mineral grease mixed with copper. Suitable for lubricating joints, bolts, gears, driveshafts and other metal parts subject to high temperatures (up to 1,000°C). Ideal for preventing seizure and making it easy to unlock threads and parts in general. Protective, anti-wear. Prevents oxidation. Does not drip.



| Item | Size |  |  |
|------|--------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|
| 9726 | 400 ml | 12 | 097260040 |



COPPER GREASE

9729

Silicone spray

Silicone lubricant and detacher. Suitable for lubricating plastic, rubber and metal parts. Protects from corrosion. Detaching, antiadhesive for plastic and rubber moulding. Antistatic, for worktops. Waterproof, protects from humidity and weather corrosion. Protective, for electric circuits. Can be used to polish wood, plastics and rubber. Solvent-free.



| Item | Size |  |  |
|------|--------|---------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|
| 9729 | 400 ml | 12 | 097290040 |



Silic SPRAY

9738

Cutting oil

Highly lubricating and protective. Suitable for milling, boring, threading, drilling and manual and automatic machine working. Highly resistant to oxidation. Water washable. Solvent-free.



| Item | Size |  |  |
|------|--------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|
| 9738 | 400 ml | 12 | 097380040 |



Cutting OIL

9740

Brake cleaner

Ideal for cleaning brake discs and pads, engines. Allows any grease and tar deposits to be removed, without leaving residue. Also suitable as a general degreaser for metal surfaces. Evaporates quickly. Does not damage plastics and rubber.



| Item | Size |  |  |
|------|--------|---------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|
| 9740 | 500 ml | 12 | 097400050 |



Brake CLEANER

9741

Multipurpose detergent/degreaser

Detergent and degreaser for dissolving grease, oil, tar, silicone and glue. Suitable for cleaning metal, hard plastic, ceramic, steel and aluminium surfaces.
Free from oil residues.



| Item | Size |  |  |
|------|--------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|
| 9741 | 400 ml | 12 | 097410040 |



Multi CLEANER

9742

Cleaner for electric and electronic contacts

Useful for cleaning and cleansing electronic contacts, circuits and electrical components in general. Its non-thick consistency allows uniform, quick distribution on treated surfaces, removing grease and dirt, without leaving oily residue. Evaporates quickly. Does not damage plastics and rubber.



| Item | Size |  |  |
|------|--------|---------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|
| 9742 | 400 ml | 12 | 097420040 |

Contact CLEANER

9743



Foam detergent

Foam detergent for all types of surfaces, tools and fabrics. Based on quaternary ammonium salts, it forms an active foam which cleans and removes dirt and grease.

Removes bad smells. No rinse required.

Not a disinfectant.



| Item | Size |  |  |
|------|--------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|
| 9743 | 500 ml | 12 | 097430050 |



Surface CLEANER

9745

Cleaner for carburetors and throttle bodies

Specific for interior and exterior cleaning of carburetors, suction ducts and throttle bodies. Totally removes carbonaceous residue, deposits and impurities. Evaporates quickly. Does not leave oily residue.



| Item | Size |  |  |
|------|--------|---------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|
| 9745 | 400 ml | 12 | 097450040 |



Carb CLEANER

9746

Air conditioner cleaner

Thick foam formulation. Suitable for industrial, civil and car air conditioners. Removes dirt, deposits and odours from ducts. Leaves a pleasant fragrance. Supplied with a straw.



| Item | Size |  |  |
|------|--------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|
| 9746 | 400 ml | 12 | 097460040 |



Clima CLEANER

9749

Air spray

Compressed gas based. Ideal for removing dust deposits from cracks, gear, electrical parts, keyboards and delicate mechanisms in general. The aerosol can with straw allows hardly accessible parts to be easily reached.



| Item | Size |  |  |
|------|--------|---------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|
| 9749 | 400 ml | 12 | 097490040 |



Air SPRAY

9752

Clear zinc

Highly covering, it is ideal for galvanizing iron parts, welding touch-ups, nuts, bolts and parts subject to weathering. Particularly resistant to oxidation and abrasion. Highly adhesive, it forms an elastic film of very light colour, similar to hot galvanizing. Can be overpainted. Also ideal as a final protectant. Does not drip.



| Item | Size |  |  |
|------|--------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|
| 9752 | 400 ml | 12 | 097520040 |


Zinc 98%

9755

Welding anti-spatter spray

Prevents slag adhesion. Makes welding easier and quicker. For use on parts that need welding and as a protector for welding torch nozzles. Makes it possible to carry out subsequent operations, e.g. painting, galvanizing and chrome-plating. Easy to remove. No fumes. Chlorinated-free.



| Item | Size |  |  |
|------|--------|---------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|
| 9755 | 400 ml | 12 | 097550040 |



Welding SPRAY

9765

De-icer spray

Removes ice and frost from windows. Also ideal for frozen locks and mechanisms. Effective down to -40°C. Nongreasy, smear-free. Does not affect treated surfaces, rubber and plastics.



| Item | Size |  |  |
|------|--------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|
| 9765 | 400 ml | 12 | 097650040 |



De-icer SPRAY

9775

Fabric waterproofing spray

Suitable for textiles and leather. Ideal for footwear, jackets and clothing in general. Allows fabrics to be waterproofed, without affecting breathability. Stain resistant. Provides improved resistance to bending and abrasion.



| Item | Size |  |  |
|------|--------|---------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|
| 9775 | 400 ml | 12 | 097750040 |

Water STOP

098510002
20 g
Bottle



9851

Instant glue

For structural joints. Based on ethyl cyanoacrylate. For adhesion of a wide range of materials, including metal, plastics, leather, wood and several other types of substrates, whether combined with each other or separate. Bonds quickly.

098510005
50 g
Bottle



098510500
5 g
Tube




098510050
500 g
Bottle



| | 9851 |
|------------------------|---------|
| Temperature range (°C) | -55/+82 |
| Viscosity (mPa.s) 25°C | 80-120 |

| Item | Size | | |
|------|-------|----|-----------|
| 9851 | 5 g | 24 | 098510500 |
| | 20 g | 12 | 098510002 |
| | 50 g | 10 | 098510005 |
| | 500 g | 1 | 098510050 |

Instant GLUE



Threadlocker

Anaerobic threadlocker for metal threads.
Prevents screws, bolts and studs from loosening due to vibrations and shocks.
Polymerizes in contact with ground metal parts and in absence of oxygen.

High chemical resistance (oils, water, gas, etc.).
Protects threads from corrosion and seizure from corrosion.

Available in 3 strength classes.

| | 9803H | 9802M | 9801L |
|-------------------------------|-----------|----------|----------|
| Temperature range (°C) | -50/+150 | -50/+150 | -50/+150 |
| Max gap fill (mm) | 0,25 | 0,15 | 0,10 |
| Handling cure time (min.) | 10/15 | 10/15 | 10/15 |
| Functional cure time (h) | 3-6 | 3-6 | 3-6 |
| Viscosity (mPa.s) 25°C | 800/1.200 | 500/800 | 500/800 |
| Breakaway torque (ISO-10964) | 35-45 Nm | 22-30 Nm | 6-10 Nm |
| Prevailing torque (ISO-10964) | 30-40 Nm | 20-25 Nm | 4-8 Nm |



9803H

Ideal for permanent locking of parts that do not need subsequent dismantling, and for passivated metal surfaces, including brass, aluminium and stainless steel.
Does not allow disassembly with hand tools.

098030002

20 ml
Bottle



098030005

50 ml
Bottle



098030025

250 ml
Bottle



| Item | Size | Tray | Bottle |
|-------|--------|------|-----------|
| 9803H | 20 ml | 12 | 098030002 |
| | 50 ml | 4 | 098030005 |
| | 250 ml | 4 | 098030025 |

HIGH RESISTANCE

9802M

Ideal for fixing parts subject to periodic maintenance, bearings and bushes. Allows dismantling by using hand tools.

098020002

20 ml

Bottle



098020005

50 ml

Bottle



098020025

250 ml

Bottle



| Item | Size | | |
|-------|--------|----|-----------|
| 9802M | 20 ml | 12 | 098020002 |
| | 50 ml | 4 | 098020005 |
| | 250 ml | 4 | 098020025 |

MEDIUM
RESISTANCE

9801L

Ideal for fixing particular light alloys which could get damaged during disassembly and for adjusting screws. Easier parts disassembly.

098010002

20 ml

Bottle



098010005

50 ml

Bottle



098010025


250 ml

Bottle



| Item | Size | | |
|-------|--------|----|-----------|
| 9801L | 20 ml | 12 | 098010002 |
| | 50 ml | 4 | 098010005 |
| | 250 ml | 4 | 098010025 |

LOW
RESISTANCE



Thread sealant

Anaerobic thread sealant for threaded metal joints. Polymerizes in contact with ground metal parts and in absence of oxygen. Provides perfect tightness to liquids and gases. Makes joints sturdier. Tolerates slight contamination by oils.

High chemical resistance (oils, water, gas). Protects threads from corrosion and seizure from corrosion.

Available in 3 strength classes.

| | 9813H | 9812M | 9811L |
|-------------------------------|---------------|---------------|---------------|
| Temperature range (°C) | -50/+200 | -50/+150 | -50/+150 |
| Max gap fill (mm) | 0,15 | 0,35 | 0,20 |
| Handling cure time (min.) | 10-15 | 12-18 | 10-15 |
| Functional cure time (h) | 3-6 | 3-6 | 3-6 |
| Viscosity (mPa.s) 25°C | 40.000/80.000 | 20.000/40.000 | 10.000/20.000 |
| Breakaway torque (ISO-10964) | 35-45 Nm | 27-35 Nm | 6-10 Nm |
| Prevailing torque (ISO-10964) | 25-35 Nm | 20-30 Nm | 4-8 Nm |



9813H

Ideal for permanent sealing of nipples, that do not need subsequent dismantling, and for passivated metal surfaces, including brass, aluminium and stainless steel. Does not allow disassembly with hand tools.



098130002

20 ml
Bottle



098130305

50 ml
Bellow bottle

098130505

50 ml
Tube

098130510

100 ml
Tube



098130525

250 ml
Tube

| Item | Size | 📦 | 🏠 |
|-------|--------|----|-----------|
| 9813H | 20 ml | 12 | 098130002 |
| | 50 ml | 6 | 098130305 |
| | 50 ml | 4 | 098130505 |
| | 100 ml | 4 | 098130510 |
| | 250 ml | 4 | 098130525 |

HIGH RESISTANCE

9812M

Ideal for sealing nipples parts subject to periodic maintenance. Allows dismantling by using hand tools.



098120002
20 ml
Bottle



098120305
50 ml
Bellow bottle

098120505
50 ml
Tube



098120510
100 ml
Tube

098120525
250 ml
Tube

| Item | Size | | |
|-------|--------|----|-----------|
| 9812M | 20 ml | 12 | 098120002 |
| | 50 ml | 6 | 098120305 |
| | 50 ml | 4 | 098120505 |
| | 100 ml | 4 | 098120510 |
| | 250 ml | 4 | 098120525 |

MEDIUM
RESISTANCE

9811L

Ideal for sealing small or fine-pitch joints. Easier parts disassembly.



098110002
20 ml
Bottle



098110305
50 ml
Bellow bottle

098110505
50 ml
Tube




098110510
100 ml
Tube

098110525
250 ml
Tube

| Item | Size | | |
|-------|--------|----|-----------|
| 9811L | 20 ml | 12 | 098110002 |
| | 50 ml | 6 | 098110305 |
| | 50 ml | 4 | 098110505 |
| | 100 ml | 4 | 098110510 |
| | 250 ml | 4 | 098110525 |

LOW
RESISTANCE



Liquid gasket

Anaerobic liquid gasket, ideal for flat mating of ground metal surfaces. Polymerizes in contact with ground metal parts and in absence of oxygen. Prevents loosening of joints and bolts and changes in thickness.

High chemical and thermal resistance (oils, water, gas).

Available in 3 strength classes.

| | 9823H | 9822M | 9821L |
|-------------------------------|-----------------|---------------|---------------|
| Temperature range (°C) | -50/+150 | -50/+150 | -50/+150 |
| Max gap fill (mm) | 0,35 | 0,35 | 0,35 |
| Handling cure time (min.) | 10/16 | 10/15 | 20/30 |
| Functional cure time (h) | 3-6 | 3-6 | 3-6 |
| Viscosity (mPa.s) 25°C | 100.000/200.000 | 40.000/70.000 | 60.000/90.000 |
| Breakaway torque (ISO-10964) | 35-45 Nm | 25-35 Nm | 7-11 Nm |
| Prevailing torque (ISO-10964) | 20-30 Nm | 20-30 Nm | 4-9 Nm |



9823H

Ideal for permanent sealing of surfaces. Also ideal for reclaiming bearing housings and worn parts. Does not allow disassembly with hand tools.



098230002

20 ml

Bottle



098230305

50 ml

Bellow bottle

098230505

50 ml

Tube

098230510

100 ml

Tube



098230525

250 ml

Tube

| Item | Size | | |
|-------|--------|----|-----------|
| 9823H | 20 ml | 12 | 098230002 |
| | 50 ml | 6 | 098230305 |
| | 50 ml | 4 | 098230505 |
| | 100 ml | 4 | 098230510 |
| | 250 ml | 4 | 098230525 |

HIGH RESISTANCE

9822M

Ideal for sealing of surfaces of parts subject to periodic maintenance. Allows dismantling by using hand tools.



098220002
20 ml
Bottle



098220305
50 ml
Bellow bottle

098220505
50 ml
Tube



098220510
100 ml
Tube

098220525
250 ml
Tube

| Item | Size | Icon | Code |
|-------|--------|------|-----------|
| 9822M | 20 ml | 12 | 098220002 |
| | 50 ml | 6 | 098220305 |
| | 50 ml | 4 | 098220505 |
| | 100 ml | 4 | 098220510 |
| | 250 ml | 4 | 098220525 |

MEDIUM
RESISTANCE

9821L

Ideal for sealing of surfaces of parts subject to frequent maintenance. Protects threads from corrosion and seizure from corrosion. Easier parts disassembly.



098210002
20 ml
Bottle



098210305
50 ml
Bellow bottle

098210505
50 ml
Tube




098210510
100 ml
Tube

098210525
250 ml
Tube

| Item | Size | Icon | Code |
|-------|--------|------|-----------|
| 9821L | 20 ml | 12 | 098210002 |
| | 50 ml | 6 | 098210305 |
| | 50 ml | 4 | 098210505 |
| | 100 ml | 4 | 098210510 |
| | 250 ml | 4 | 098210525 |

LOW
RESISTANCE



Locker

Anaerobic locker for metal threads. Prevents loosening due to vibrations and shocks. Polymerizes in contact with ground metal parts and in absence of oxygen. Increases torque transmitted between shaft and hub, removing corrosion from friction. High thermal and chemical resistance (oils, water, gas). Available in 3 strength classes.

| | 9833H | 9832M | 9831L |
|-------------------------------|----------|-------------|----------|
| Temperature range (°C) | -50/+180 | -50/+180 | -50/+150 |
| Max gap fill (mm) | 0,15 | 0,25 | 0,10 |
| Handling cure time (min.) | 10/15 | 12/20 | 10/15 |
| Functional cure time (h) | 3-6 | 3-6 | 3-6 |
| Viscosity (mPa.s) 25°C | 400/700 | 2.000/4.000 | 500/800 |
| Breakaway torque (ISO-10964) | 35-45 Nm | 25-35 Nm | 6-10 Nm |
| Prevailing torque (ISO-10964) | 30-40 Nm | 18-28 Nm | 4-8 Nm |



9833H

Ideal for fixing parts that do not need subsequent dismantling. Also suitable for fixing already installed devices that are difficult to dismantle. Does not allow disassembly with hand tools.



098330002

20 ml
Bottle



098330005

50 ml
Bottle



098330025

250 ml
Bottle

| Item | Size | 📦 | 🏢 |
|-------|--------|----|-----------|
| 9833H | 20 ml | 12 | 098330002 |
| | 50 ml | 4 | 098330005 |
| | 250 ml | 4 | 098330025 |

HIGH
RESISTANCE

9832M

Ideal for fixing parts subject to periodic maintenance.
Allows dismantling by using hand tools.

 098320002


20 ml
Bottle



 098320005



50 ml
Bottle



 098320025

250 ml
Bottle



| Item | Size |  |  |
|-------|--------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|
| 9832M | 20 ml | 12 | 098320002 |
| | 50 ml | 4 | 098320005 |
| | 250 ml | 4 | 098320025 |

MEDIUM RESISTANCE


9831L

Ideal for fixing small parts subject to frequent
maintenance. Easier parts disassembly.

 098310002


20 ml
Bottle



 098310005



50 ml
Bottle



 098310025

250 ml
Bottle



| Item | Size |  |  |
|-------|--------|---------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|
| 9831L | 20 ml | 12 | 098310002 |
| | 50 ml | 4 | 098310005 |
| | 250 ml | 4 | 098310025 |

LOW RESISTANCE

Siliconic sealants

9841N

Black acetic-reticulation silicone sealant, resistant to high temperatures, with convenient pressure dispenser (pressure pack)

Withstands temperatures up to 240°C. Enables permanent elastic sealing. Replaces preformed gaskets. The convenient dispenser allows easy (one-coated), accurate, uniform spreading of the product. Polymerizes by reacting with atmospheric moisture and forms an elastic, durable gasket. Ideal for oil sumps, oil pumps, housings, gearboxes, engine parts that are not subject to high pressure and applications that require resistance to high temperatures. Perfectly adheres to most non-porous substrates, including glass, coated wood, ceramic and enamel. Not suitable for PE, PP, PC, PMMA, PTFE, soft plastics, neoprene and bituminous substrates. Cannot be painted.



NEW

240°C

9841R



Red acetic-reticulation silicone sealant, resistant to high temperatures, with convenient pressure dispenser (pressure pack)



Withstands temperatures up to 300°C. Enables permanent elastic sealing. Replaces preformed gaskets. The convenient dispenser allows easy (one-coated), accurate, uniform spreading of the product. Polymerizes by reacting with atmospheric moisture and forms an elastic, durable gasket. Ideal for oven and furnace doors, plates, heating systems, outlets, thermostats, pumps, heating pipes, engine parts that are not subject to high pressure and applications that require resistance to high temperatures. Perfectly adheres to most non-porous substrates, including glass, coated wood, ceramic and enamel. Not suitable for PE, PP, PC, PMMA, PTFE, soft plastics, neoprene and bituminous supports. Cannot be painted.



NEW

300°C

| Item | Size |  |  |
|-------|--------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|
| 9841N | 200 ml | 12 | 098410120 |

| Item | Size |  |  |
|-------|--------|---------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|
| 9841R | 200 ml | 12 | 098410020 |

Black SEAL

Red SEAL

Liquids

9881U

Industrial alkaline detergent for ultrasonic tank

Industrial alkaline detergent, concentrated, water-based. For ultrasonic cleaning and other purification processes. Allows spare parts and metal pieces in general (injectors, carburetors, valves etc.) to be accurately and effectively cleaned. Removes oil, grease, lubricants, residues of glue, resin and wax. Also suitable for cleaning aluminium parts. pH 13.5

Recommended amount:

3-4% (1:30) - light to normal dirt

5% (1:20) - heavy dirt

Operating temperature: > 40°C

for aluminium: max. recommended temperature 65°C.

After treatment, rinse with water.



9882R

Selective rust remover liquid



Water-based selective rust remover liquid for iron, steel, stainless steel, cast iron and chrome platings. Removes top oxidized layer, without affecting underlying metal.

Dilution: from pure to max. 1:1.

Minimum operating temperature: 15°C.

Operating times: 30' - 24/48h (for heavy rust). Biodegradable and 100% water-soluble.



| Item | Size |  |  |
|-------|------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|
| 9881U | 1 L | 1 | 098810010 |

| Item | Size |  |  |
|-------|------|---------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|
| 9882R | 1 L | 1 | 098820010 |

ULTRASONIC CLEANER

RUST CLEANER

The images are for reference only. Beta Utensili S.p.A. reserves the right to update and upgrade its product range without notice.



www.beta-tools.com