

**8040EZ**
**lifting eye bolts, DIN 580 galvanized**

CE

**DIN 580:2010-09**
**TECHNICAL DATA**


- safety factor: 6
- heat treatment: normalizing
- traceability code


**LABORATORY TESTS**

- chemical analysis
- metallographic analysis
- tensile test

**AVAILABLE CERTIFICATES**

- Technical product specifications
- Test report UNI EN10204 type 2.2
- Inspection certificate UNI EN10204 type 3.1
- CE Declaration of Conformity



		art.	Ø mm	$\frac{E}{\phi}$ mm	WLL kg	E mm
*	<b>080400406</b>	8040EZ M6	M6	1	90	11
	<b>080400408</b>	8040EZ M8	M8	1,25	140	13
	<b>080400410</b>	8040EZ M10	M10	1,5	230	17
	<b>080400412</b>	8040EZ M12	M12	1,75	340	20,5
*	<b>080400414</b>	8040EZ M14	M14	2	480	20,5
	<b>080400416</b>	8040EZ M16	M16	2	700	27
*	<b>080400418</b>	8040EZ M18	M18	2,5	930	27
	<b>080400420</b>	8040EZ M20	M20	2,5	1200	30
*	<b>080400422</b>	8040EZ M22	M22	2,5	1450	30
	<b>080400424</b>	8040EZ M24	M24	3	1800	36
*	<b>080400427</b>	8040EZ M27	M27	3	2400	41
	<b>080400430</b>	8040EZ M30	M30	3,5	3200	45
*	<b>080400433</b>	8040EZ M33	M33	3,5	3900	54
*	<b>080400434</b>	8040EZ M33F	M33F	2	3900	54
	<b>080400436</b>	8040EZ M36	M36	4	4600	54
*	<b>080400437</b>	8040EZ M36F	M36F	3	4600	54
	<b>080400442</b>	8040EZ M42	M42	4,5	6300	63
*	<b>080400443</b>	8040EZ M42F	M42F	3	6300	63
	<b>080400448</b>	8040EZ M48	M48	5	8600	68
*	<b>080400449</b>	8040EZ M48F	M48F	3	8600	68
	<b>080400456</b>	8040EZ M56	M56	5,5	11500	78
*	<b>080400457</b>	8040EZ M56F	M56F	4	11500	78
	<b>080400464</b>	8040EZ M64	M64	6	16000	90
*	<b>080400465</b>	8040EZ M64F	M64F	4	16000	90